

HV48100 Cabinets



Features



Optimized Footprint



Optimized for Adaptability

Suitable for multiple models: HV48100, V5°, V5°α



Scalable on Demand



Rugged Reliability, Effortless Setup

	HV48100 8S	HV48100 12S	HV48100 15S
Compatible Battery Models*	HV48100	HV48100, V5°, V5°α	HV48100, V5°, V5°α
Max. Capacity	8 × HV48100 BMU (1P8S – 40.96 kWh)	12 × HV48100 BMU (1P12S – 61.44 kWh) 13 × V5° / V5°α (66.56 kWh)	15 × HV48100 BMU (1P15S – 76.8 kWh) 2P7S – 71.68 kWh 16 × V5° / V5°α (81.92 kWh)
Dimensions (W x D x H)	23.6 × 25.2 × 61.2 inch / 600 × 640 × 1555 mm	23.43 × 26.77 × 82.68 inch / 595 × 680 × 2100 mm	1054 × 626 × 1463 mm / 41.5 x 24.7 x 57.6 inch
Weight	197.5 lbs / 89.6 kg	304.2 lbs / 138 kg	278.9 lbs / 126.5 kg
Enclosure Rating	IP20		

* When installing the V5° / V5°α modules in HV48100 12S / 15S cabinet, remove the side panels to facilitate heat dissipation. HV48100 8S cabinet is not recommended for use with V5° / V5°α modules.

