

Rack- Mounted LFP Battery Module

Tier 1

Automotive
Grade Cell



E-BOX 48100R TE+



Safe & Reliable

- Tier 1 Automotive Grade A LiFePO₄ cells
- Self-designed & Field-proven BMS



Long-lasting

- ≥6000Cycles @ 90%DoD



Scalable

- From 5.12kWh to 491.52kWh



Compact, Flexible and Easy Install



E-BOX 48100R TE+ Enclosures

E BK1

- Up to 6 × E-BOX 48100R
- Floor Mount
- SGCC



Electrical

Nominal Voltage	51.2 V
Voltage Range	47.5 V ~ 57.6 V
Nominal Capacity	100 Ah
Nominal Energy	5.12 kWh
Recommended Charge / Discharge Current	50 A (2.56 kW dc)
Maximum Charge / Discharge Current	50 A (2.56 kW dc)
Peak Discharge Current	102 A (5.22 kW@15s)

General

Chemistry	LFP
Communication Protocol	CAN / RS485
Dimensions (L x W x H)	17.3 x 24.4 x 4.6 inch (2.6 U) / 440 x 620 x 117 mm (2.6 U)
Weight	112.5 lbs / 51 kg
Ambient Temperature	14 °F ~ 122 °F / -10 °C ~ 50 °C
Round-Trip Efficiency	≥ 95%
Cycle Life ¹	≥ 6000 Cycles
Warranty	10 Years

Certifications

Certifications	UL9540 Ed.2 (2020), UL9540A, UL1973, CEC, SGIP, CE, IEC62619, UN38.3
----------------	--

1. Test Condition: 0.5 C, 25 °C @90% DoD.

